

SPECIFICATIONS

MODEL : LF900-C(900W)



ODA

TECHNOLOGIES
www.odacore.com

Parameter		Specifications	
Operating range(@0℃ ~ 40℃)	Voltage	1 to 600.0V	Maximum 606.0
	Current	0 to 30.0A	Maximum 31.5
	Max Power	0 to 900.0W at 40℃	(derated to 720.0W at 50℃)
MODE SPECIFICATIONS			
CC MODE	RANGE	HI 0 to 31.5A LOW 0 to 3.0A	
	RESOLUTION	LOW 0.1mA	HI 1.0mA
	Accuracy	± 0.1%± 6.0mA (after 30sec wait)	
CV MODE	RANGE	HI 1 to 606.0V LOW 0 to 60.0V	
	RESOLUTION	LOW 1.0mV	HI 10.0mV
	Accuracy	± 0.05%± 120.0mV	
CR MODE	RANGE	0.2 to 6kΩ	
	RESOLUTION	100mΩ	
	Accuracy	±0.5%±200mΩ (<50mS)	
CP MODE	RANGE	0 to 900.0W at 40℃	
	RESOLUTION	100mW	
	Accuracy	±0.5%±90mW (<50mS)	
ON/OFF MODE	RANGE	0 to 31.5A	
	RESOLUTION	1.0mA	
	Accuracy	±0.1%±6.0mA (after 30sec wait)	
	ON/ OFF TIME	100mS~250H59M59S990mS(10mS Unit)	
	REPEAT	1~65000	
FUSE MODE	RANGE	0 to 31.5A	
	RESOLUTION	1.0mA	
	Accuracy	±0.1%±6.0mA (after 30sec wait)	
	FUSE TIME	100mS~250H59M59S990mS(10mS Unit)	
BAT MODE	CC	RANGE	0 to 31.5A
		Accuracy	±0.1%±6.0mA (after 30sec wait)
	CR	RANGE	0.2 to 6kΩ
		Accuracy	±0.5%±200mΩ (<50mS)
	CP	RANGE	0 to 900.0W at 40℃
		Accuracy	±0.5%±90mW (<50mS)
	END Volt		0 to 606.0V
	END CAP		0.01 to 5000AH
CYCLE MODE	CC	RANGE	0 to 31.5A
		Accuracy	±0.1%±6.0mA (after 30sec wait)
	CV	RANGE	0 to 606.0V
		Accuracy	±0.05%±120.0mV
	CYCLE TIME		100mS~250H59M59S990mS(10mS Unit)
	STEP		1~100Step
	REPEAT		1~65000
DYNAMIC MODE	MEMORY CH		2CH
	Freq Range		0.5Hz ~ 10KHz
	Freq Accuracy		3%
	Duty Cycle Range		3~ 97%(<200μS)
	Duty Cycle Accuracy		6% of setting± 2%
	CC	Range	0 to 31.5A
		Accuracy	A ± 0.1%± 6.0mA B ± 0.2%± 12.0mA
	CV	Range	0 to 606.0V
		Accuracy	A ± 0.05%± 120.0mV B ± 0.1%± 240.0mV
SLEW RATE(typical values; 5%~ 95%)			
CC,CR,CP MODE		<200uS(0 to 30.0A)	
CV MODE		<2mS(0 to 600.0V)	
PROTECTION			
OVP		648.0V(<10mS)	
OCP		32.4A(<10mS)	
OPP		972.0W(<10mS)	
OTP		100℃(Heatsink Temp)	
Short& Open	Shor	100mΩ(max), 50mΩ(typical)	
	Open	≥20kΩ	
Ripple& Noise	Current	4mA(rms)/ 40mA(p- p)	
	Voltage	6mV(rms)	
Remote Sensing		3Vdc between sense And load input	
INPUT AC		110/220V(S/W) ± 10% 50~ 60Hz/300mA POWER MAX :66W	
Remote Interface		RS- 232C & RS- 485 (TCP/IP Option)	
Cooling		Isolation DC FAN	
Dimensions (19- inch 2U Standard)		426mm(W) * 88mm(H) *470mm(D) (900~1200W)	
Weight		15ka(Net weight) / 16ka(Gross weight)	