



DAP3000 Series

AC/DC Power Supply

- DAP3125: Output voltage up to 12V, Maximum rated output of 5A AC or DC
- DAP3248: Output voltage up to 24V, Maximum rated output of 8A AC or DC
- Lightweight & compact design for portability and space efficiency.
- Large clear illuminated display ensures clear visibility in bright or dim environments.
- Built-in cooling fan maintains stability during prolonged high-load operation.
- Dual short-circuit & overload protection with response for safety.
- USB key slot unlocks voltage limits when inserted and locks them when removed.
- Lock & overload indicators provide instant visual status feedback.

+ Specifications

The specifications based upon the instrument having run for at least 30 minutes continuously, under the specified operating environment

Specification	DAP3125	DAP3248
DC Output Voltage Range	0-12V	0-24V
DC Output Resolution	0.1V	0.1V
AC Output Voltage Range	1-12V	1-24V
AC Output Resolution	0.1V	0.1V
Maximum Current	5A	8A
Smoothed DC	Yes	
Regulated Output	Yes	
Input Voltage	100-230V $\pm 10\%$	
Working Temperature Range	0-40°C	
Storage Temperature Range	-20-60°C	
Humidity	< 90%RH No condensation	
Fuse	250V, F2AL	250V, F3AL
Weight	1.5kg	1.7kg
Dimensions(L*W*H)	230mm×160mm×105mm	


+ Accessories The accessories subject to final delivery.



Power Cord



User Manual



Fuse



USB Key